

Tel +49 (0) 831 / 960 398-0 Fax +49 (0) 831 / 960 398-10 E-mail: <u>info@kombitec.de</u> www.kombitec.de

Technical data-sheet Workstation HA-XX-xxx

Name and address of manufacturer:

KombiTec GmbH

Westendstraße 5

D-87488 Betzigau / Germany

Tel: +49 (0) 831 / 960 398 - 0 Fax: +49 (0) 831 / 960 398 - 10





Tel +49 (0) 831 / 960 398-0 Fax +49 (0) 831 / 960 398-10 E-mail: <u>info@kombitec.de</u> www.kombitec.de

Benefits:

- Cost-effectiveness standard solution
- Duties and custom combinable
- Extensive installation components available as a "standard" modules
- Standard width: 1.200 mm or 1.600 mm
- On demand several welding stations from crossbeams with roller conveyors
- Also "ESD"-version available
- Suitable for all Kombi Tec's welding heads, welding guns and inverters
- Pneumatic-components from Fa. SMC, FESTO or Bosch Rexroth selectable
- With glare bright illumination of the work area
- Lighting and sockets separately switchable
- By footrest and chair used as a "seat workstation"
- In combination with small controllers semi- and fully automated
- Optional: with extensions for automated feeding and removal of components

Application areas:

Suitable for laboratory-working station for sample-production up to professional equipped, handling-optimised working station for mass-production.

- Suitable as a "stand-alone"-solution or as an integrated component in productionchain
- available with "monitored N.i.O.-box"

Technical changes:

Technical modification and price changes without notices. All dimensions are in "mm". No liability can be accepted for printing errors.



Tel +49 (0) 831 / 960 398-0 Fax +49 (0) 831 / 960 398-10 E-mail: <u>info@kombitec.de</u>

www.kombitec.de

Technical data:

Main dimension (w/d/h): 1.200 mm x 750 mm x 1.215 mm / 2.230 mm

Weight: approx. 40 kg – 150k g, add. application

Connection: Current: 220 V / 50 Hz for lightning


Current: depending to power-source and PLC


pressed air


Environment: Industrial environment, clean, dry, frost-free

Not suitable for EX-environment!

Temperature-range: $0^{\circ}C - 60^{\circ}C$







Picture: Dimension Working-station HA-1200 without fixing/ mountings



Tel +49 (0) 831 / 960 398-0 Fax +49 (0) 831 / 960 398-10 E-mail: info@kombitec.de www.kombitec.de

Workstation HA-XX-xxx Options for configuration:

Glare-free illumination **HA-XX-xxx**

Switched outlet in various **National versions selectable HA-1200-xxx**

Arm matched to the powersource HA-XX-xxx

Pneumatic-components from SMC, Festo or Bosch-Rexroth

Workstation in "ESD-version" available

Fixing for all KombiTec-powersources and transformers

