



# Metzner AM 2000

Innovative Cutting and Stripping Technology

### Metzner AM 2000 Flexibility and Efficiency



The automatic cutting- and stripping machine Metzner AM 2000 is specially designed for your requirements: Process reliability, flexible and fast production, minimum set-up times, as well as user-friendliness, low noise level and a standard scope of equipment which is unique in this class, define the benefit profile of these machines.

The Metzner AM 2000 cuts and strips wires and multi-conductor round cables of up to 6mm<sup>2</sup> cross-section and 6mm outer cable diameter to perfect size. With the "strip in several steps" function, the machine can also strip off longer lengths of insulation. Even window stripping is among the standard functions offered by these




machines. The basic version of the AM 2000 already supports the connection of marking and labelling devices, as well as the control with a PC/laptop for machining complex batches in cable assembly.

#### Standard cable straightening device

The standard AM 2000 models come equipped with a high-quality cable straightening device. Especially in this cross-sectional range, cables and wires are often processed from coils which are wound around a small radius. Only the Metzner standard straightening device guarantees that the wires and cables are straightened as required for later processing.

Metzner	
---------	--



#### "End-of-material" shut-down

A standard "end-of-material" shut-down function offers the big advantage of automated and non-monitored operation. The machine detects the end of the processed material and interrupts the selected job automatically.

## Expandable to an automatic production line

The Metzner AM 2000 series is prepared to multiple expansions. According to your production requirements the AM 2000 is ready to be combined with motorized dereelers, prefeeders, hot-stamp units or ink-jet printers as well as cable stackers or coilers.

Performance	Metzner AM 2000/4	
Wire size range, stranded	0.14 – 6mm² (AWG 25 – 10)	
Wire size range, solid	0.14 – 2.0mm² (AWG 25 – 14)	
Outer wire diameter max.	6mm	
Pull-off length max. 1. side	30mm	
Pull-off length max. 2. side	100mm	
Programmable total length	10 mm – 100 m	
Feeding speed	0 – 60 m/min, infinitely adjustable	
Features		
Cutting system	V-blade cutting system	
Drive	3~Stepper motor	
Interfaces optional	Dereeleres, prefeeders, cable stackers, cable coilers, ink-jet printers, hot-stamp cable markers, RS 232	
Technical Data		
Dimensions (LxWxH)	410 x 575 x 645mm	
Electrical connection	230 V, 50/60 Hz, 1 kW	
Noise level	< 70 dB(A)	
Weight	50 kg	

Specifications are subject to change without notice.

Metzner Maschinenbau GmbH

Messerschmittstraße 30 89231 Neu-Ulm | Germany Phone: +49 731 40199-0 Fax: +49 731 40199-33 Email: sales@metzner.com

### www.metzner.com